

## **OPTION SHEET FOR NANOCOM ANT430**

Customer Product ID:(	optional, enter your reference here)
Order number:	Example Use:
1. Configuration Table	Option B = Yes  Option B = No
Antenna type	
Standard for 2U/3U	
Short antennas for 1U	
Frequency Option	
NanoCom ANT430	430 - 440 MHz
	395 - 405 MHz
Misc. Option – option to mount a small Flight Preparation Panel, view datasheet	
Mount a NanoUtil FPP Top-S	

## 2. Disclaimer

The information in this document is subject to change without notice and should not be construed as a commitment by GomSpace. GomSpace assumes no responsibility for any errors that may appear in this document.

In no event shall GomSpace be liable for incidental or consequential damages arising from use of this document or the software and hardware described in this document.





Product name: NanoCom ANT430

Document No.: 1010592

Revision: 4.0

Author: ROBB

Approved by: MVE

Approval date: 18-06-2020

## **Confidentiality Notice**

This document is submitted for a specific purpose as agreed in writing and contains information, which is confidential and proprietary. The recipient agrees by accepting this document, that this material will not be used, transferred, reproduced, modified, copied or disclosed in whole or in part, in any manner or to any third party, except own staff to meet the purpose for which it was submitted without prior written consent.

GomSpace © 2020