

# OPTION SHEET FOR NANOPOWER DSP




Customer Product ID: \_\_\_\_\_ (optional, enter your reference here)

Order number: \_\_\_\_\_

Example Use:

Option A	<input checked="" type="checkbox"/>	= Yes
Option B	<input type="checkbox"/>	= No

## 1. Configuration Table

Please check the DSP variant			
	135 deg	135 deg reverse	90 deg
			
DSP variant	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Please check the connector type of the DSP Interstage PCBA	
Straight connector	<input type="checkbox"/>
Right angle connector	<input type="checkbox"/>

Please check the voltage of the antenna release knives (usually battery voltage)			
	5V	16V	32V
Knife Voltage	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Product name: NanoPower DSP

Document No.: 1028196

Revision: 1.0

Author: KERA

Approved by: JBJ

Approval date: 12 October 2020

## Confidentiality Notice

This document is submitted for a specific purpose as agreed in writing and contains information, which is confidential and proprietary. The recipient agrees by accepting this document, that this material will not be used, transferred, reproduced, modified, copied or disclosed in whole or in part, in any manner or to any third party, except own staff to meet the purpose for which it was submitted without prior written consent.

GomSpace © 2020

## 2. Disclaimer

The information in this document is subject to change without notice and should not be construed as a commitment by GomSpace. GomSpace assumes no responsibility for any errors that may appear in this document.

In no event shall GomSpace be liable for incidental or consequential damages arising from use of this document or the software and hardware described in this document.