

# OPTION SHEET FOR NANOPOWER ACU-200

Customer Product ID: \_\_\_\_\_ (optional, enter your reference here)

Order number: \_\_\_\_\_

Example Use:

Option A	✓	= Yes
Option B		= No

## 1. Configuration Table

CSP address \_\_\_\_\_ (default is 2)

Battery voltage range - select one	
12.0 – 16.8 V	
24.0 – 33.6 V	

Over voltage stop point is by default set to 2-3 V above max. battery voltage.

Dock position				
	X1	X2	X3	X4
Position				

Mark which position the ACU is to be fitted. Double check with the P60 Dock option sheet module configuration table.

## 2. Disclaimer

The information in this document is subject to change without notice and should not be construed as a commitment by GomSpace. GomSpace assumes no responsibility for any errors that may appear in this document.

In no event shall GomSpace be liable for incidental or consequential damages arising from use of this document or the software and hardware described in this document.

Product name: NanoPower ACU-200

Document No.: 1014027

Revision: 4.0

Author: MABO

Approved by: BGS

Approval date: January 2020

## Confidentiality Notice

This document is submitted for a specific purpose as agreed in writing and contains information, which is confidential and proprietary. The recipient agrees by accepting this document, that this material will not be used, transferred, reproduced, modified, copied or disclosed in whole or in part, in any manner or to any third party, except own staff to meet the purpose for which it was submitted without prior written consent.

GomSpace © 2019