

QUALIFICATION CERTIFICATE

NanoSense FSS

Reference: 1028518
Revision: 1.0
Date: 30-09-2021

Document Title:	Gs-Qtct-NanoSense FSS		
Reference:	1028518	Document Class	Qtct
Revision number:	1.0	Date:	30-09-2021

Release Table:

Action	Name	Function	Signature	Date
Prepared / Owned by:	Sebastian Andersen	Junior Engineer	SEAN	29/06/2021
Verified / Reviewed by:	Morten Bisgaard	Head of Spacecrafts and solution	MBD	30/09/2021
Approved by:	Lars Vestergaard	Technology Manager	LAV	30/09/2021

Document Change Log

Revision	Date	Name	Description
1.0	30-09-2021	SEAN	Initial release

Table of Contents

1. INTRODUCTION	4
1.1 PURPOSE	4
1.2 REFERENCES STANDARDS.....	4
2. QUALIFICATION TESTS	5
2.1 STRUCTURAL AND MECHANICAL TESTS	5
2.2 THERMAL STRESS TEST	5
2.3 THERMAL VACUUM TEST	6
2.4 RADIATION TID TESTS.....	6
2.5 FLIGHT HERITAGE	6
3. CONCLUSION	6

1. Introduction

1.1 Purpose

This document describes the environmental qualification tests carried out on the following product:

- 200275 – NanoSense FSS

In the following sections, the tests and the corresponding test results are described.

1.2 References Standards

Table 1 presents the tests included in the Qualification Program with reference to ECSS documentation.

Table 1: Reference Standards

Test		ECSS/ESCC Reference
Structural and Mechanical	Random Vibration	ECSS-E-ST-10-03C
	Sinusoidal Vibration	ECSS-E-ST-10-03C
	Mechanical Shock	ECSS-E-ST-10-03C
	Quasi static	ECSS-E-ST-10-03C
Thermal	Thermal Ambient	ECSS-E-ST-10-03C
	Thermal Vacuum	ECSS-E-ST-10-03C
Radiation TID		ESCC 22900
Thermal Stress		ECSS-Q-ST-70-38C

2. Qualification tests

It is hereby certified that the product mentioned above has been subjected to the tests executed in relation to the standards mentions in section 1.2

2.1 Structural and Mechanical tests

Sinusoidal Vibration		
	Frequency [Hz]	Level [g]
Sine Sweep Vibration	5-8	20mm peak-peak
	8-100	4,5
Sweep rate: 2 Octaves per minute		

Random Vibration		
	Frequency [Hz]	ASD Level [g^2/Hz]
Sine Sweep Vibration	20	0,057
	20-50	+3,39dB/Oct
	50-800	0,16
	800-2000	-6dB/Oct
	2000	0,026
	Overall	14,1G RMS
Duration: 120 Seconds on each axis		

Mechanical shock		
	Frequency [Hz]	Level [g]
Mechanical shock	2000 Hz	1500G
No. of test axis: X,Y,Z		

Mechanical Quasi-Static			
Sine Burst	Frequency [Hz]	Cycles	Level[g]
	15	19	11,2G
No. of burst: 8 ($\approx 10sec$)			

Remarks: None


2.2 Thermal Stress Test

Thermal Stress		
Temperature Range:		
Action	Temperature [$^{\circ}C$]	Duration [Minutes]
Heat	100	(10 $^{\circ}C/min$)
Dwell	100	15
Cool	-55	(10 $^{\circ}C/min$)
Dwell	-55	15
Repeat	-	-
Repeats: 500 cycles		

Remarks: None

2.3 Thermal Vacuum Test

Test condition: Test as part of fully integrated 3U spacecraft.



Remarks: None

2.4 Radiation TID Tests

Total Ionizing Dose		
Dose Rate:	24,6kRad/h	
Dose	54,8min	20 kRad (SI)
Annealing	>24 hours	25 degC
Aging	168 hours	85 degC

Remarks: None

2.5 Flight Heritage

The NanoSense FSS is TRL 9 and has extensive flight heritage including GomSpace missions like GOMX-3 and GOMX-4 as well as many customer missions.

3. Conclusion

The NanoSense FSS is tested according to the above-mentioned conditions and is fully functional and have the expected performance.

This certificate ensures that performance, test condition and test equipment are according to GomSpace quality.