



GomSpace A/S  
Langagervej 6  
9220 Aalborg E

## **NANOCOM SDR MK3**

### Qualification Certificate

Reference: 1047305  
Revision: 1.3  
Date: 2025-08-22

<b>Document Title:</b>	NanoCom SDR MK3 Qualification Certificate		
<b>Reference:</b>	1047305	<b>Document Class</b>	QTCT
<b>Revision number:</b>	1.3	<b>Date:</b>	2025-08-22

**Release Table:**

Action	Name	Function	Initials / Signature	Date
Prepared / Owned by:	Dannie Toft Nielsen	Test Engineer	DTN	2022-12-09
Verified / Reviewed by:	Martin Siegumfeldt	Product Owner	MNS	2023-03-28
Approved by:	Lars Vestergaard	Technology Manager	LAV	2023-05-25

**Document Change Log (Not mandatory)**

Revision	Date	Initials	Description
0.1	2022-12-09	DTN	Initial draft
1.0	2023-01-30	DTN	Reviewed and approved
1.1	2023-05-17	DTN	Added Thermal Stress Test
1.2	2023-05-25	DTN	To align revision with IFS
1.3	2025-08-22	LAV	Flight Heritage information updated

**References**

Reference	Document title	Document number	Revision, Date
[RD-1]	GomSpace Qualification Program	1012670	Rev. 2.3, 2023-03-24
[RD-2]	gs-qtrp-NanoCom SDR HP MK3 Structural and Mechanical Vibration Test Report	1042055	Rev. 1.0, 2022-08-09
[RD-3]	gs-qtrp-NanoCom SDR HP MK3 Mechanical Shock Test Report	1046352	Rev. 1.0, 2022-11-28
[RD-4]	gs-qtrp-NanoCom SDR HP MK3 TVAC Test Report	1044571	Rev. 1.0, 2022-11-09
[RD-5]	gs-qtrp-NanoCom SDR HP MK3 Radiation TID Test Report	1043889	Rev. 1.0, 2022-11-17
[RD-6]	gs-qtrp-NanoCom SDR HP MK3 Thermal Stress Test Report	1047119	Rev. 1.0, 2023-03-14

## TABLE OF CONTENTS

1. QUALIFICATION TESTS .....	4
1.1 PURPOSE.....	4
1.2 PRODUCT.....	4
1.3 VIBRATION TESTS.....	5
1.4 SHOCK TESTS.....	6
1.5 THERMAL VACUUM TESTS.....	7
1.6 RADIATION TID TESTS.....	8
1.7 THERMAL STRESS TEST.....	9
1.8 FLIGHT HERITAGE .....	10

## 1. Qualification Tests

### 1.1 Purpose

This document describes the environmental qualification tests which is carried out on this specific product(s). In the following sections, the tests and the corresponding test results are described.

### 1.2 Product

Manufacturer Name: GomSpace  
Product Name: NanoCom SDR MK3  
Product Number: 107903

Product variants can consist of the following subproducts:

Product Name	Product Number
NanoDock MK3	108687
NanoMind Z7045 MK3	108688
NanoMind Z7030 MK3	108689
NanoCom TR600 MK3	108686

### 1.3 Vibration Tests

The product has been subjected to the following tests.

**Tests:** Random Vibration  
Sinusoidal Vibration  
Quasi-static / Sine burst

**Conditions:** Product is mounted in a 6U GomSpace structure which is mounted inside a GomSpace Qualification POD. It is tested under the following test conditions.

Test Description	Test Requirements
Random Vibration	20Hz, 0.026G2/Hz 20-50Hz, +6 dB/oct 50-800Hz, 0.16G2/Hz 800-2000Hz, -6 dB/oct 2000Hz, 0.026G2/Hz Overall, 14.1Grms
Sinusoidal Vibration	5-8Hz, 20mm pp 8-100Hz, 4.5G
Quasi-static / Sine burst	30Hz, 15G, 19 cycles / 7 loaded cycles

**Remarks:** None

**Conclusion:** The NanoCom SDR MK3 is tested according to the above-mentioned conditions. The visual mechanical inspection and electrical / functional tests are passed with no remarks. This certificate ensures that performance, test condition and test equipment are according to GomSpace quality.

## 1.4 Shock Tests

The product has been subjected to the following tests.

**Tests:** Shock

**Conditions:** Product is mounted in the fixture for the GomSpace shock bench. The device is exposed to three impacts at each axis, X, Y and Z. It is tested under the following test conditions.

Test Description	Test Requirements
Shock Response Spectrum (SRS):	100Hz, 40G 1000Hz, 1000G 2000Hz, 1500G 10000Hz, 1500G +/- 6db from the nominal shock >50% of the measured shock are above nominal shock

**Remarks:** None

**Conclusion:** The NanoCom SDR MK3 is tested according to the above-mentioned conditions. The visual mechanical inspection and electrical / functional tests are passed with no remarks. This certificate ensures that performance, test condition and test equipment are according to GomSpace quality.

## 1.5 Thermal Vacuum Tests

The product has been subjected to the following tests.

**Tests:** Thermal Vacuum (TVAC)

**Conditions:** Product is mounted in a 6U GomSpace structure, prepared with thermocouples and harness, installed in the TVAC chamber for test. The temperature range defined in the table below refers to the thermal interface of the product during test to ensure its operating temperatures are within specifications. It is tested under the following test conditions.

Test Description	Test Requirements
Temperature	-40 to 53°C
Pressure	1e-5 mbar
Cycles	8
Dwell time	2 hours

**Remarks:** None

**Conclusion:** The NanoCom SDR MK3 is tested according to the above-mentioned conditions and is fully functional and have the expected performance. This certificate ensures that performance, test condition and test equipment are according to GomSpace quality.

## 1.6 Radiation TID Tests

The product has been subjected to the following tests.

**Tests:** Radiation TID (Total Ionizing Dose)

**Conditions:** The complete product is mounted at a plate for TID testing, prepared with harness and necessary logging equipment.  
It is tested under the following test conditions.

Test Description	Test Requirements
Method	Direct (Online)
Rate	Low dose – 36 to 360 rad(Si)/hour
Total dose	>20 krad
Condition	Biased at room temperature
Annealing	>24 hours
Ageing	>168 hours

**Remarks:** Actual dose - 3.04Gy/h, total dose 210Gy (21krad) is to ensure all components at PCBAs has reached the level of 20krad.

**Conclusion:** The NanoCom SDR MK3 is tested according to the above-mentioned conditions. The electrical / functional tests performed the are passed. This certificate ensures that performance, test condition and test equipment are according to GomSpace quality.

## 1.7 Thermal Stress Test

The product has been subjected to the following tests.

**Tests:** Thermal Stress (Accelerated Lifetime)

**Conditions:** Product is prepared with thermocouples and installed at the shelf of the Thermal Stress chamber. It is tested under the following test conditions.

Test Description	Test Requirements
Temperature – hot plateau	100°C +5 /-0°C
Temperature – cold plateau	-55°C +0 /-5°C
Cycles	150
Dwell time	15 minutes

**Remarks:** None

**Conclusion:** The NanoCom SDR MK3 is tested according to the above-mentioned conditions. The visual mechanical inspection and electrical / functional tests are passed with no remarks. This certificate ensures that performance, test condition and test equipment are according to GomSpace quality.

## 1.8 Flight Heritage

The NanoCom SDR MK3 is at TRL 9 passing the qualifications tests, and have flight heritage since August 2024 on various customer missions.

The product is an update of the existing NanoCom SDR V2, which has extensive flight heritage. Furthermore, a prototype of the NanoCom SDR MK3 has flight heritage since June 2021, flying on a customer mission.