

QUALIFICATION CERTIFICATE

NanoMind A3200

Reference: 1028506
Revision: 1.1
Date: 16-02-2026

Document Title:	Gs-Qtct-NanoMind A3200		
Reference:	1028506	Document Class	Qtct
Revision number:	1.1	Date:	16-02-2026

Release Table:

Action	Name	Function	Signature	Date
Prepared / Owned by:	Sebastian Andersen	Junior Engineer	SEAN	29/09/2020
Verified / Reviewed by:	Lars Vestergaard	Technology Manager	LAV	09-11-2021
Approved by:	Brian Madsen	Test Manager	BRMA	09-11-2021

Document Change Log

Revision	Date	Name	Description
1.0	09-11-2021	SEAN	Initial release
1.1	16-02-2026	PHK	Updated to cover all 4 variants:

Table of Contents

1. INTRODUCTION	4
1.1 PURPOSE.....	4
1.2 REFERENCES STANDARDS	4
2. QUALIFICATION TESTS	5
2.1 STRUCTURAL AND MECHANICAL TESTS.....	5
2.2 THERMAL STRESS TEST.....	6
2.3 THERMAL VACUUM TEST	7
2.4 RADIATION TID TESTS	7
2.5 FLIGHT HERITAGE.....	7
3. CONCLUSION.....	7

1. Introduction

1.1 Purpose

This document describes the environmental qualification tests carried out on the following products:

- 200284 - NanoMind A3200 BSP SW
- 111619 - NanoMind A3200 CDH
- 112873 - NanoMind-A3200 SDK
- 112872 - NanoMind-A3200 SDK PWM from VAUX
- 103409 - NanoMind A3200 BSP SW PWM from VAUX
- 111425 - NanoMind A3200-ADCS PWM from VAUX

In the following sections, the tests and the corresponding test results are described.

1.2 References Standards

Table 1 presents the tests included in the Qualification Program with reference to ECSS documentation.

Table 1: Reference Standards

Test	ECSS/ESCC Reference	
Structural and Mechanical	Random Vibration	ECSS-E-ST-10-03C
	Sinusoidal Vibration	ECSS-E-ST-10-03C
	Mechanical Shock	ECSS-E-ST-10-03C
	Quasi static	ECSS-E-ST-10-03C
Thermal	Thermal Ambient	ECSS-E-ST-10-03C
	Thermal Vacuum	ECSS-E-ST-10-03C
Radiation TID	ESCC 22900	
Thermal Stress	ECSS-Q-ST-70-38C	

2. Qualification tests

It is hereby certified that the product mentioned above has been subjected to the tests executed in relation to the standards mentions in section 1.2

2.1 Structural and Mechanical tests

Sinusoidal Vibration		
	Frequency [Hz]	Level [g]
Sine Sweep Vibration	5-8	20mm peak-peak
	8-100	4,5
Sweep rate: 2 Octaves per minute		

Random Vibration		
	Frequency [Hz]	ASD Level [g^2/Hz]
Sine Sweep Vibration	20	0,026
	50	0,16
	800	0,16
	2000	0,026
	Overall	14,1G RMS
Duration: 120 Seconds on each axis		

Mechanical Quasi-Static			
Sine Burst	Frequency [Hz]	Cycles	Level[g]
	15	19	11,2G
No. of burst: 8 (~ 10sec)			

Shock Response Spectrum (SRS) Qualification Levels	
Shock levels based on Q = 10 quality factor	
Frequency [Hz]	Level [g] (+/- 6db)
100	40
1000	1000
2000	1500
10000	1500

Remarks: None

2.2 Thermal Stress Test

Thermal Stress		
Temperature Range:		
Action	Temperature [°C]	Duration [Minutes]
Heat	100	(10°C/min)
Dwell	100	15
Cool	-55	(10°C/min)
Dwell	-55	15
Repeat	-	-
Repeats: 500 cycles		

Remarks: None

2.3 Thermal Vacuum Test

Thermal Vacuum Qualification levels		
Temperature range: -45°C to +55°C		
Pressure level: < 1.0 x 10 ⁻⁵ mbar		
Number of Cycles: 8		
Thermal Vacuum Test	CFT	Temperature [°C]
	1	22
	2	55
	3	-45
	4	5
	5	55
	6	5
	7	-45
8	22	
UTC Date 20/03 – 27/03		

Remarks: None

2.4 Radiation TID Tests

Total Ionizing Dose		
Dose Rate:	24,6kRad/h	
Dose	54,8min	20 kRad (SI)
Annealing	>24 hours	25 degC
Aging	168 hours	85 degC

Remarks: None

2.5 Flight Heritage

The NanoMind A3200 is TRL 9 and has extensive flight heritage including GomSpace missions like GOMX3 as well as many customer missions.

3. Conclusion

The NanoMind A3200 is tested according to the above-mentioned conditions and is fully functional and have the expected performance.

This certificate ensures that performance, test condition and test equipment are according to GomSpace quality.